

Application No.: 09/851,367

Atty. Dkt.: ZL327-01008

Page 2 of 21

In the Claims

- B1
Cont'd*
- Claim 1 (Currently Amended): A recessed unit equipment luminaire comprising:
- a housing;
 - a battery;
 - a charging/emergency switching circuit electrically connected to said battery;
 - a directional lamp mounted within said housing,
 - said directional lamp having a light source, a reflectorized bowl and a cover,
 - said directional lamp being electrically connected to said battery through said
 - charging/emergency switching circuit; and
 - a cover having an opening to allow light from said directional lamp to be directed therethrough.
- Claim 2 (Original): The unit equipment luminaire of claim 1 further having a reflector assembly mounted within said housing along the light path between said directional lamp and said cover opening, said reflector assembly having a reflective surface which redirects a portion of the light emitted from said directional lamp.
- Claim 3 (Original): The unit equipment luminaire of claim 2 wherein said reflector assembly is substantially semi-frustoconical in shape and is oriented with a wide end proximate to said directional lamp.
- Claim 4 (Original): The unit equipment luminaire of claim 3 wherein said reflector assembly has a plurality of planar reflecting surfaces which approximate said semi-frustoconical shape.
- Claim 5 (Original): The unit equipment luminaire of claim 4 wherein said reflector assembly has a central reflector section and side reflector sections, said central reflector section sloping

Application No.: 09/851,367

Atty. Dkt.: ZL327-01008

Page 3 of 21

downward from the top of said directional lamp to said cover opening, said side reflector sections located on either side of said central reflector section, said side reflector sections sloping downward and outward from said central reflector section to said cover opening.

Claim 6 (Original): The unit equipment luminaire of claim 5 wherein said central reflector section has a plurality of reflecting surfaces which redirect light to specific regions.

Claim 7 (Original): The unit equipment luminaire of claim 1 further having a louvered lens placed in the light path between said directional lamp and said cover opening.

B
Cont'd
Claim 8 (Original): The unit equipment luminaire of claim 2 wherein said cover opening is circular, said reflector assembly is in a fixed relation with said directional lamp, and said reflector assembly further has a circular front edge which is rotatably engaged by said cover along said circular.

Claim 9 (Original): The unit equipment luminaire of claim 7 further having:
a second directional lamp mounted within said housing, said second directional lamp being electrically connected to said battery through said charging/emergency switching circuit;
a second reflector assembly mounted within said housing along the light path between said directional lamp and said cover opening, said reflector assembly having a circular front edge and a reflective surface which redirects a portion of the light emitted from said second directional lamp;
said cover further having a second circular opening which rotatably engages said second reflector assembly circular front edge.

Claim 10 (Currently Amended): A luminaire for illuminating an ~~oblong~~ a conical shaped area comprising:

Application No.: 09/851,367

Att. Dkt: ZL327-01008

Page 4 of 21

a housing;

a directional lamp mounted within said housing,

said directional lamp being aimed at said ~~oblong~~ conical shaped area;

a cover having an opening to allow light from said directional lamp to be directed toward said ~~oblong~~ conical shaped area; and

a reflector assembly mounted within said housing along the light path between said directional lamp and said cover opening, said reflector assembly being substantially semi-frustoconical in shape oriented with a wide end proximate to said directional lamp and having a reflective surface which redirects a portion of the light emitted from said directional lamp toward said ~~oblong~~ conical shaped area.

Claim 11 (Original): The luminaire of claim 10 wherein said reflector assembly has a plurality of planar reflecting surfaces which approximate said semi-frustoconical shape.

Claim 12 (Original): The luminaire of claim 11 wherein said reflector assembly has a central reflector section and side reflector sections, said central reflector section sloping downward from the top of the directional lamp to the cover opening, said side reflector sections located on either side of said central reflector section, said side reflector sections sloping downward and outward from said central reflector section to said cover opening.

Claim 13 (Currently Amended): The luminaire of claim 12 wherein said central reflector section has a plurality of reflecting surfaces which direct light to specific regions in said ~~oblong~~ conical shaped area.

Claim 14 (Original): The luminaire of claim 10 further having a louvered lens placed in the light path between said directional lamp and said cover opening.

Application No.: 09/851,367

Atty. Dkt.: ZL327-01008

Page 5 of 21

Claim 15 (Original): The luminaire of claim 10 wherein said cover opening is circular, said reflector assembly is in a fixed relation with said directional lamp, and said reflector assembly further has a circular front edge which is rotatably engaged by said cover along said circular opening, whereby an alternate area may be illuminated by rotating said reflector assembly and said directional lamp with respect to said cover.

Claims 16-20 (Canceled)

Claim 21 (Original): A unit equipment luminaire for recessed mounting behind the plane of a wall for illuminating a path of egress area comprising:

*B1
Cancel*

- a housing mounted behind an opening in the plane of the wall;
- a battery;
- a charging/emergency switching circuit electrically connected to said battery;
- a substantially semi-frustoconical reflector assembly having a wide end and a narrow end;
- a wall mount lens having a collecting reflector;
- a directional lamp mounted within said housing,
- said directional lamp being located at said reflector assembly wide end and aimed generally toward said collecting reflector, said directional lamp being electrically connected to said battery through said charging/emergency switching circuit; and
- a cover mounted over said wall opening, said cover having an opening to allow light from said collecting reflector to exit said housing.

Claim 22 (Original): The unit equipment luminaire of claim 21 wherein said reflector assembly has a plurality of planar reflecting surfaces which approximate the semi-frustoconical shape.

Application No.: 09/851,367

Atty. Dkt.: ZL327-01008

Page 6 of 21

Claim 23 (Original): The unit equipment luminaire of claim 22 wherein said reflector assembly has a central reflector section and side reflector sections, said side reflector sections located on either side of said central reflector section, said side reflector sections sloping outward from said central reflector section.

*B1
Conc'd*

Claim 24 (Original): The unit equipment luminaire of claim 21 wherein said collecting reflector is concave shaped and extends from the top of said wide end of said reflector assembly to the bottom of said narrow end of said reflector assembly, said collecting reflector having an inner edge which follows the curvature of said reflector assembly and an outer edge which extends outward from said plane of the wall a distance proportional to the inward extension of said inner edge.

Claim 25 (Original): A unit equipment housing and battery box assembly comprising:
a shallow rectangular shaped housing having a bottom wall, a back wall, and an open front, said bottom wall having an opening along the intersection of said bottom wall and said back wall; and
a battery box having a front wall, a back wall, side walls extending between said front wall and said back wall, a closed bottom, an open top, and a flange extending around the upper edge of the front and side walls;
said battery box being received within said housing bottom wall opening such that the bottom of said battery box flange contacts the inner surface of the housing bottom wall along the periphery of the bottom wall.

Claim 26 (Original): A unit equipment housing assembly comprising:
a shallow rectangular shaped housing having a bottom wall, and side walls, said bottom wall having an opening along the intersection of said bottom wall and said back wall, each side wall

Application No.: 09/851,367

Atty. Dkt.: ZL327-01008

Page 7 of 21

having an inward projections which is parallel with said housing bottom wall thereby forming a channel between said projection and said bottom wall;

a battery box having a front wall, a back wall, side walls extending between said front wall and said back wall, and an open top, a flange extending around the upper edge of the front and side walls, and a wedge shaped protuberance extending outward and upward from said flange, said back wall extending upward above the upper edge of the front and side walls and having a mortise type slot in said upward extension; and

B1
cond
a thin rectangular chassis for supporting a charger/emergency switching circuit, said chassis having a tenon type projection along a back edge of the chassis;

said battery box being received within said housing bottom wall opening such that the bottom of said battery box flange contacts the inner surface of said housing bottom wall along the periphery of said bottom wall opening; said chassis being received within said housing channels such that said a front edge of said chassis is held in place by the back edge of said battery box wedge shaped protuberance and said tenon projection mates with said mortise slot.

Claim 27 (Original): A housing for mounting behind the plane of a wall or ceiling, said housing comprising:

a front portion, said front portion to lie substantially in the plane of the wall or ceiling;

at least one side wall having a front edge lying along said front portion, said side wall having a thickness gauge formed on the outside surface thereof, said thickness gauge indicating distance from said front edge; and

a plurality of break-away tabs located around the periphery of said front portion, said break-away tabs extending outward along the plane of said front portion.

Application No.: 09/851,367

Atty. Dkt.: ZL327-01008

Page 8 of 21

Claim 28 (Currently Amended): A fully recessed unit equipment luminaire comprising:

at least one battery;

a battery box having walls for containing said battery and an opening for receiving said battery;

a housing having walls defining a chamber and an open front, one of said walls having an opening, said housing and said battery box being attached such that said housing wall opening is in alignment with said battery box opening;

an a charger chassis having a charger/emergency switching circuit mounted thereto, said charger chassis being received within and attached to said housing over said battery box opening such that the said charger chassis provides a barrier between said housing chamber and said battery;

a directional lamp electrically connected to said battery through said charger/emergency switching circuit, said lamp also is received within said housing; and

a cover closing said housing open front, said cover having a light exit aperture positioned to allow light from said lamp to illuminate an area external to said luminaire.

Claim 29 (Previously Added): A recessed unit equipment luminaire, comprising:

A housing, a battery, a switching circuit, a cover having a first and a second opening, a first reflector assembly in said first opening of said cover and a second reflector assembly in said second opening of said cover, wherein said first reflector assembly has a first directional lamp and wherein said second reflector assembly has a second directional lamp, said first and said second directional lamp electrically connected to said battery through said switching circuit.

Claim 30 (Previously Added): The recessed equipment luminaire of claim 29 wherein said first and said second reflector assembly are rotateably mounted on said cover.

Application No.: 09/851,367

Atty. Dkt.: ZL327-01008

Page 9 of 21

Claim 31 (Previously Added): The recessed equipment luminaire of claim 30 wherein each of said first and said second reflector assemblies have a central reflector section and a first and second side reflector section, said central reflector section extending from said cover to said directional lamp, said first and second side reflector sections extending upwardly from said central reflector section to said cover opening.

Claim 32 (Previously Added): The recessed equipment luminaire of claim 31 wherein said first and second reflector assembly are semi-frustoconical.

Claim 33 (Previously Added): The recessed equipment luminaire of claim 30 wherein said first and said second reflector assembly each have a collecting reflector formed therein.

Claim 34 (Currently Amended): A recessed unit equipment luminaire comprising a housing, a battery box retained in said housing, a switching circuit, a first and a second removable reflector assembly rotateably mounted on a cover attached to said housing, said first reflector assembly having a first reflector formed therein, said second reflector assembly having a second reflector retained therein, said first reflector assembly having a first directional lamp and said second reflector assembly having a second directional lamp, said first and said second directional lamp electrically connected to said battery by said switching circuit.

Claim 35 (Previously Added): The luminaire of claim 34 wherein said first reflector assembly has a light exit aperture and wherein said second reflector assembly has a light exit aperture, said first reflector of said first reflector assembly being frusto-conical and sloping downward from said exit aperture to said first lamp, said second reflector of said second reflector assembly being frusto-conical and sloping downward from said exit aperture to said second lamp.

Application No.: 09/851,367

Atty. Dkt.: ZL327-01008

Page 10 of 21

B' end

Claim 36 (Previously Added): The luminaire of claim 34 wherein each of said first and said second reflector assembly has a generally concave collecting reflector extending to an exit aperture, said collecting reflector emitting light through said exit aperture in an elongated area shape.

Claim 37 (Previously Added): The luminaire of claim 34 wherein said battery box is retained within an aperture in a side wall of said housing.

Claim 38 (Previously Added): The luminaire of claim 34 wherein said cover further has a peripheral outer edge designed for recess mounting of said luminaire in a wall, said cover mounted on an exterior surface of said wall, said housing, battery box and switching circuit maintained on an interior surface of said wall.
